



Aldridge Corporation Pty. Ltd.

P 1300 662 514
F 1300 662 517
E hpma@bigpond.com
Unit 18, 38 Powers Road, Seven Hills, NSW 2147

High Performance Membranes

www.hpma.com.au

HPM-MULTIPRIME

Latex-Based Liquid Primer

FEATURES AND BENEFITS	RECOMMENDED FOR
<ul style="list-style-type: none"> - Australian made - Non flammable - Environmentally friendly - Easy cleanup - Negligible odour & toxicity - Easy to use and economical - Long shelf life 	-



Description:

HPM-Multiprimer is a latex based liquid which has been specifically designed for priming a variety of substrates prior to the use of Aldridge Corporation's range of water-based waterproofing membranes. HPM-Multiprimer will eliminate dust and porosity of plasterboard, fibro, cement render, porous concrete & timber floors.

Surface Preparation

Surfaces must be clean, firm, dry, sound and smooth. All grease, oil, wax, curing compound, dust, plaster droppings and paint must be removed prior to the application of HPM-Multiprimer. Building boards, timber and particleboard flooring must be fixed in accordance with the manufacturer's directions. Timber and particleboard flooring must be sanded prior to the application of HPM-Multiprimer. Cement render must be allowed to cure for at least 7 days and concrete 28 days.

Packaging

20 Litres.

Coverage

Approx. 6m² per litre depending on the surface.

Application

HPM-Multiprimer must be applied on a well-prepared surface using brush, roller, sponge or airless spray. Allow to dry for at least 30min. Prior to the application of a water-based membrane.

Safety Precautions

This product is non-toxic and has no known harmful effects. It is advisable to wear gloves and use good occupational health and safety practices to avoid personal contact. For more detailed information refer to product MSDS.

Shelf Life

Unopened containers can be stored for up to 12 months in a cool, dry and weatherproof environment.

HPM-MULTIPRIME

TECHNICAL DATA