

BOSTIK 9222

Membrane Primer

DESCRIPTION

Bostik 9222 is based on bitumen modified with rubber and resins to produce a specifically formulated primer for bitumen waterproof membranes. Bostik 9222 has a higher solids content than Bostik 9225.

FEATURES & BENEFITS

- Excellent adhesion to concrete, timber, steel, block or brick work.
- Brush, roller or spray application.
- Cost effective.

PACKAGING

Supplied in 20 litre drums, ex stock, 200 litres on request. Colour is Black.

USES:

- Adhering self adhesive or bitumen/rubber membranes to concrete, block or brick work (eg Boscoseal16)
- Multiple coatings will provide a 'simple' low flexibility membrane.

PRECAUTIONS

- Substrates must be dry before application.
- Highly flammable in liquid state.
- Not recommended for use in confined spaces. Areas to be primed must be well vented.
- **Do not use** as a primer for polyurethane liquid membranes such as Bostik Boscoseal PU or Bostik Ultraseal

CLEAN UP

Wipe up immediately with cloth or rags whilst still wet or with petroleum based solvent.

P.A.T.S (Pretested Adhesion To Substrate) Programme

Bostik offer a service in which a program has been established to eliminate potential field problems by pre-testing Bostik adhesives with samples of building materials to which the adhesive will be applied. This service is available on large projects where pre-application testing will aid in determining the proper surface preparation method to achieve optimum adhesion. Consult a Bostik representative for further information.

HEALTH AND SAFETY

On contact, uncured primer causes irritation. Gloves and protective goggles must be worn during application and use.

- Avoid contact with skin, eyes and avoid breathing in vapour.
- Wear protective gloves when mixing or using
- If poisoning occurs, contact a doctor or Poisons Information Centre.
- If swallowed, do not induce vomiting. Give a glass of water.
- If skin contact occurs, remove contaminated clothing and wash skin thoroughly for a minimum of 15 minutes and see a doctor.
- For more detailed information refer to Material Safety Data Sheet.

BOSTIK 9222 PRIMER

ITEM NO.	STOCK SIZE
189200	BOSTIK 9222 MEMBRANE PRIMER 20L

The representations and recommendations regarding the products are based on tests which we believe to be reliable. However, no guarantee of their accuracy can be made because of the great range of field conditions and variations encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with a limited warranty only, and on the condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik Australia Pty Ltd be liable to anyone except for replacement of the products or refund of the purchase price.

ALL SALES ARE EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS OF SALE OF BOSTIK AUSTRALIA PTY LTD



BOSTIK
AUSTRALIA PTY LTD
Phone: +61-3-9279 9333
Fax: +61-3-9279 9240

SYDNEY
Phone: 02 8825 3488
Fax: 02 8825 3411

BOSTIK
NZ LIMITED
Phone: +64-4-567 5119
Fax: +64-4-567-5412

ADELAIDE
Phone: 08 8244 0511
Fax: 08 8244 0522

FOR FURTHER INFORMATION

BOSTIK
SINGAPORE PTE LTD
Phone: +65-863 4088
Fax: +65-863 4077

PERTH
Phone: 08 9258 6218
Fax: 08 9258 7687

(ABN 79 003 893 838)

BOSTIK
(MALAYSIA) SDN BHD
Phone: +606 764 3246
Fax: +606 764 3248

BRISBANE
Phone: 07 3260 2206
Fax: 07 3260 2123

Product:	Bostik 9222 Primer
Issue Date:	October 2001
Issue No:	1
Division:	Industrial
Total Pages:	1