



HPM-Multiprimer

Technical Data Sheets

HPM-Multiprimer is a latex based liquid which can be used for priming a variety of substrates prior to the use of Aldridge Corporation's HPM range of waterbased waterproofing membranes

HPM-Multiprimer will eliminate dust and porosity of plasterboard, fibro, cement render, porous concrete and timber floors

Features & Benefits

- Reduces Porosity
- Makes Membrane application easy
- Stops premature drying of membranes
- Eliminates Dust
- Expands open time

Recommended For

- Porous Concrete
- Cement render/Blockwork
- Fibro/Plasterboard
- Brickwork/ Hebel blocks
- Timber
- Particleboard

Surface Preparation

Surfaces must be clean, firm, dry sound and smooth. All grease, oil, wax, curing compound, dust, plaster droppings and paint must be removed prior to the application of **HPM-Multiprimer**. Building boards, timber and particleboard flooring must be fixed in accordance with the manufacturer's directions. Timber and particleboard flooring must be sanded prior to the application of **HPM-Multiprimer**. Cement render must be allowed to cure for at least 7 Days and concrete 28 days.

Application

HPM-Multiprimer must be applied on a well prepared surface using brush, roller, sponge or airless spray. Allow to dry for at least 30min. Prior to the application of waterbased membrane.

Packaging

15 Litres

Coverage

Approx. 6m² per litre depending on the surface

Safety Precautions

This product is non-toxic and has no known harmful effects. It is advisable to wear gloves and use good occupational health and safety practices to avoid personal contact. For more detailed information refer to product MSDS.

Shelf Life

Unopened containers can be stored for up to 12 months in a cool, dry and weatherproof environment

Limitations

- Do not use on non-porous surfaces such as existing tiles, waterproofing membranes or steel trowel finished floors
- Only suitable on porous surfaces